

890PG Utility Saw

The 890PG hydraulic utility chain saw offers cutting depths up to 25" in ductile iron, cast iron, PVC, HDPE, Insituform lining and even Asbestos* concrete pipe. The deep cutting ability of the 890PG with PowerGrit utility chain, allows the operator to make a single cut from one side meaning less excavation is required. Change the way you cut pipe! Also the 890PG is capable of operating the full line of 890F4 ProFORCE™ concrete cutting chains, meaning you can use the saw on masonry, stone, and even reinforced concrete - perfect for pipe taps, utility vaults, bridge work, and other utility applications.




890PG PRODUCT SPECIFICATIONS

	8 GPM/30 LPM	12 GPM/30 LPM
Weight	27.3 lbs/24.3 kg with 15-in/38 cm bar/chain and 1' hose whips	
Bar length	up to 25 in/63 cm	
Motor Speed	6100 rpm	6500 rpm
Powerhead dimensions	23 in (58.5 cm) length 10.5 in (26.5 cm) height 9.5 in (24 cm) width	
Torque	122 in-lbs/13.8 Nm	170 in-lbs/19.2 Nm
Horsepower	11.5 hp/8.6 kW	17.5 hp/13 kW
Hydraulic Supply	8 gpm/30 lpm, 2500 psi/172.5 bar	12 gpm/45 lpm, 2500 psi/172.5 bar
Noise Level	98 dB @ 3 ft (1 m) (Sound pressure level) 107 dB @ 3 ft (1 m) (Sound power level)	
Vibration Level	2.0 m/second ² (front handle) 6.0 m/second ² (rear handle)	
Water Supply	Minimum 20 psi (1.5 bar)	

* Product data shown is rated based on maximum input conditions and efficiency assumptions and may vary dependent on power supply.

* Asbestos is a hazardous material, known to cause serious respiratory diseases. Cutting into asbestos can release asbestos fibers into the air. Always research and follow the correct safety procedures, including applicable national and state or provisional occupational health and safety regulations, and protect yourself and those around you from asbestos-related disease. Always arrange for the material to be removed safely by a qualified person. ICS is not responsible for exposure to asbestos caused by use of this product.



ICS, BLOUNT INC. HEADQUARTERS | 4909 SE International Way Portland, OR 97222-4679 | PHONE 800.321.1240 · FAX 503.653.4393

© Copyright 2014-2015 ICS, Blount Inc. Privacy statement specifications subject to change without notice.

Pricing and specifications subject to change without notice. All rights reserved. ICS, WallWalker, SpeedHook, SealPRO, FORCE4 and PowerGrit are registered trademarks of ICS. The best way to cut concrete, DCT, TSS, ProFORCE and TwinMAX are trademarks of ICS.1214